

DECLARATION OF PERFORMANCE - DOP

#DOP23323/0074

1 / 3

Product name

WTF P Perfect Silicone

- 1. Type of product**
100% silicon, 1-component, Meko-free

- 2. Application**
Sealant for the application in facades, sanitary and wet area joints
EN 15651-1: F INT-EXT-CC 25LM
EN 15651-2:G CC 25LM
EN 15651-3: S XS1

- 3. Manufacturer / Importer**
Rakennuskemia LTD, Kerkkolankatu 17, FIN-05800 Hyvinkää. Finland

- 4. System of assessment of constancy of performance**
3 plus 3

- 5. Harmonised Standard**
EN 15651-1: 2012-12, EN 15651-2; 2012-12, EN 15651-3: 2012-12

- 6. Notified body**
Quality control certification body #1213 has conducted tests according to EN 15651-1-3 and given test and classification reports.

- 7. When dealing with DOP for construction product, of what an European technical assessment is given:**
Not applicable

- 8. Essential characteristics**
EN 15651-1:2012
Pretreatment:
Method A (ISO 8340)
Substrate:
Mortar M2 (no primer)
Glass(no primer)
Anodised aluminium (no primer)

DECLARATION OF PERFORMANCE - DOP

#DOP23323/0074

2 / 3

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire	Class E	EN 15651-1:2012
Release of chemicals dangerous to the environment and health	NPD	
Water tightness and air tightness	Water tightness and air tightness	
Resistance to flow	≤ 3 mm	
Loss of volume	≤ 10 %	
Tensile properties at maintained water exposure	NF	
Tensile properties (secant modulus) at -30°C	≤ 0,9 MPa	
Tensile properties at maintained extension at -30 oC	NF	
Durability	Pass	

EN 15651-2:2012

Pretreatment:

Method A (ISO 8340)

Substrate:

Mortar M2 (no primer)

Glass(no primer)

Anodised aluminium (no primer)

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire	Class E	EN 15651-2:2012
Release of chemicals dangerous to the environment and health	NPD	
Water tightness and air tightness	Water tightness and air tightness	
Resistance to flow	≤ 3 mm	
Loss of volume	≤ 10 %	
Adhesion and cohesion after exposure to heat, water and artificial light	NF	
Elastic Recovery	≥ 60 %	
Tensile properties (secant modulus) at -30°C	≤ 0,9 MPa	
Tensile properties at maintained extension at -30 °C	NF	
Durability	Pass	

DECLARATION OF PERFORMANCE - DOP

#DOP23323/0074

3 / 3

EN 15651-3:2012
Pretreatment:
Method A (ISO 8340)
Substrate:
Glass(no primer)
Anodised aluminium (no primer)

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire	Class E	EN 15651-3:2012
Release of chemicals dangerous to the environment and health	NPD	
Water tightness and air tightness	Water tightness and air tightness	
Resistance to flow	≤ 3 mm	
Loss of volume	≤ 20 %	
Tensile properties at maintained water exposure	NF	
Microbiological growth	0	
Durability	Pass	

9. The performance of the product identified in the beginning is in conformity with the declared performance in point

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 3.

Signed for and on behalf of the manufacturer by:

Ville Aalto

Product Manager
Rakennuskemia LTD
05.12.2022